



Futuristic design combines with efficient heat to deliver a slim fireplace that is almost as easy to install as hanging a picture on the wall.

LENNOXTM
HEARTH PRODUCTS

DAVE LENNOX
*signature*TM
COLLECTION



Scandium™ shown

■ The Radium™, Scandium™ and Elite™ CVF catalytic vent-free fireplaces from the Dave Lennox *Signature™* Collection reflect the ultimate in innovation. Less than eight inches deep, they're ideal for contemporary living spaces, high-rises, lofts or any space where venting cannot be installed, and the slim and modern design makes installation as easy as hanging a picture on a wall. Patented* catalytic technology cleans the hot air as it leaves the combustion chamber and, because these fireplaces boast a fuel efficiency approaching 100%, nearly all the heat produced is distributed directly into the living space. These sleek offerings create a unique fire presentation that is sure to amaze and mesmerize. ■

*U.S. Patent 5,678,534



STANDARD FEATURES

Approaching 100% efficiency lowers fuel costs

Vent-free configuration allows installation almost anywhere a gas connection is available

With less than eight inches in depth and no special framing requirements, unit installation is about as easy as hanging a picture on a wall

Patented catalytic technology cleans hot air as it leaves the combustion chamber

Adjustable flame height and heat intensity

Radium meets BTU and exhaust temperature requirements allowing installation in bedrooms*

Burns natural gas or propane

20-year limited warranty

Backed by the Good Housekeeping Seal

**Check local codes*



Elite™ CVF shown

RADIUM™



Front View



Side View

ELITE™ CVF



Front View



Side View

SCANDIUM™




Front View



Side View

PERFORMANCE INFORMATION

Percent of Allowable Per ANSI Z21.11.2



Test results by independent laboratories confirm that Radium™ and Scandium™ catalytic vent-free gas fireplaces meet or exceed current and applicable nationally recognized standards and recommendations for indoor air quality and are among the cleanest-burning unvented products when measuring allowable levels of combustion byproducts such as carbon monoxide and nitrogen dioxide.

PRODUCTS YOU CAN COUNT ON

Lennox is committed to providing you with high-quality products. A qualified dealer can help you find the right product to give you years of comfort and enjoyment.

SPECIFICATIONS

MODEL	Max. BTU	Min. BTU	FIREPLACE		
			WIDTH	HEIGHT	DEPTH
Radium™	NG 8,870	5,110	35-3/8"	27-1/4"	7-1/2"
	LP 7,500	5,110			
Scandium™	NG 11,950	6,820	41-1/2"	21"	7"
	LP 10,235	6,820			
Elite™	NG 6,825	3,412	23-13/16"	27-5/32"	6-1/4"
	LP 5,800	3,412			

IMPORTANT NOTES:

As with any heating appliance, fireplace or stove, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and appliance location.

Diagrams, illustrations and photographs are not to scale—consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

LENNOX™

HEARTH PRODUCTS



© Lennox Industries Inc. 2010

Visit us at www.lennox.com, or contact us at 1-800-9-LENNOX.



Tested & Listed By



Portland Oregon USA

OMN-Test Laboratories, Inc.

Report number: 317-6-04-5

Report number: 317-6-05-5

